

机型：YF-2512G/YF-3220G UV平板机 UV Flatbed Printer

机器简介

- ◆ 多种喷头配置，可选理光、柯尼卡喷头
A variety of print head configuration, Ricoh, Konica
- ◆ 高精度自动测高系统
Automatic height detection system
- ◆ 灵敏的小车防撞系统
Anti-collision system
- ◆ 智能恒温墨路系统
Intelligent constant temperature ink system
- ◆ 采用LED冷温固化技术，更长使用寿命，更低能耗
LED UV water cooling system, high performance, low energy consumption
- ◆ 智能墨水液位报警提示系统
Intelligent ink level alarm system



行业应用

Industry Application



电子3C
Electronic



KT板
KT Board



标识标牌
Signage



亚克力灯箱
Acrylic



背景墙
Background Wall



礼盒
Gift Box

机器参数

Machine parameters

机型/Model		YF-2512G UV 平板机 YF-2512G UV Flatbed Printer				YF-3220G UV 平板机 YF-3220G UV Flatbed Printer		
喷头/Printhead		Ricoh GEN5灰度级压电喷头 Ricoh GEN5 Industrial Grayscale Print Head				Ricoh GEN5灰度级压电喷头 Ricoh GEN5 Industrial Grayscale Print Head		
喷头数量/Print Head number		2-8				2-8		
打印模式/Print Mode		4C/6C、4C/6C+W、4C/6C+W+V、2*4C/6C+W、3*4C						
打印尺寸/Print Width		2500mm x 1200mm				3200mmx 2000mm		
打印速度 Print Speed (sqm/h)	模式 Print Mode	4C	2*4C	3*4C	4C	2*4C	3*4C	
	草图 4PASS	22 m ² /h	44 m ² /h	66 m ² /h	24 m ² /h	48 m ² /h	72 m ² /h	
	标准 6PASS	18 m ² /h	36 m ² /h	54 m ² /h	20 m ² /h	40 m ² /h	60 m ² /h	
	高精 8PASS	14 m ² /h	28 m ² /h	42 m ² /h	16 m ² /h	32 m ² /h	48 m ² /h	
打印分辨率/Print Resolution		720*1800DPI						
介质类型 Media Type		玻璃、亚克力、木板、瓷砖、金属板、PVC板、发泡板、3C产品、皮料等材料 Glass,Acrylic, Wood, Ceramic, Metal Sheet, PVC Sheet, Plastic,3C product and etc.						
介质厚度 Media Thickness		材料厚度≤100mm;车头升降≤100mm Max.100 mm						
墨水类型 Ink Type		LED环保型UV墨水(不含VOC) UV Curing Ink (None VOC)						
特殊墨水 Special Ink		LED白色墨水或透明光油可选 Optional White Ink or Varnish						
固化系统 Curing System		LED灯固化系统 LED Curing System						
输入格式/File Format		TIFF/PDF/JPES/EPS						
RIP软件 RIP		Photoprint/Onyx/Caldera/Colorget						
数据传送接口/Data Connector		USB2.0						
输入电源 Power		220VAC(±10%) 单相, 50/60HZ 220VAC(±10%) Single Phase, 50/60 HZ						
机器功耗/Power Consumption		5.5KW				6.0KW		
机器尺寸/净重Machine Size/N.W.		4.75m(L)*2.1m(W)*1.4m(H)/1550KG				5.4m(L)*2.95m(W)*1.47m(H)/2300KG		
包装尺寸/毛重Packing Size/G.W.		4.9m(L)*2.28m(W)*1.75m(H)/1650KG				5.8m(L)*3.2m(W)*1.75m(H) /2400KG		
环境要求 Environment Requirement		独立、洁净、低尘、少光照、通风良好的工作间环境温度:20℃ - 28℃, 相对湿度:40% - 60% seperated, clean, low dust, well-ventilated,environmental temperature:20℃-28℃ relative humidity:40%-60%						

注：以上技术参数如有变动恕不另行通知，以实际设备为准。
Above specification will be changeable without notice